

VDO360

SABER SPECIFICATIONS

Video Format: USB3 and DVI--1080p59.94/50/29.97/25; 720p59.94/50/29.97/25;
DVI--1080i 59.94/50.

Video Output: USB3.0 & DVI-I

Sensor: 1/2.3 inch 4K UHD CMOS sensor

Lens: f3.9 -46.1mm (12X zoom), E1.8 - 2.8

Angle of View: 72.5°

Rotation Angle: Pan Rotation: $\pm 170^\circ$; Tilt rotation: -30° - $+90^\circ$, supports inverted installation

Rotation Speed: Pan Speed: 0.1° - 150° /s; Tilt speed: 0.1° - 80° /s

Preset: 10 via IR remote setting, (255 via RS232) , preset accuracy : 0.2°

Auto/Manual White Balance, Auto/Manual Exposure (Iris, Shutter)

Control signal port: SB UVC FECC and 8 pin mini DIN--RS232--VISCA/Pelco-D/Pelco-P protocol

Power voltage: DC12V/2.0A; power port: HEC3800.

Max consumption:24W

Working temperature: -5 - 45°C

Storage temperature: -20 - 60°C

Net weight: 1.5KG

Dimension: 220x190x173 mm



3432 South River Terrace, Edgewater MD 21037
855-443-2492 or 307-200-7448
www.vdo360.com